

Rx Collection for Healthcare

Cosmos | Crossings | Forest | Infinity | Strait



The vinyl surfaces in the Rx Collection were developed to meet the performance and aesthetic requirements of a space. These products provide a unique solution, featuring a vulcanized composition rubber backing fusion-bonded to a contemporary heterogeneous vinyl sheet. Available as standard rolls, these products offer seamless, easy-to-maintain surfaces that reduce the risk of injury associated with falls, offer sound control, and provide comfort underfoot.

Markets

- PT/OT
- Healthcare
- Senior Care

Benefits

- Significantly reduces surface-generated noise
- Ergonomic
- Reduces force of impact related to falls
- Slip resistant
- Ease of maintenance
- Stain and chemical resistant
- Durable
- Indentation resistant

Applications

- Ambulatory Surgery
- Behavioral Health
- Clinics
- Emergency Department
- In-Patient Corridors
- In-Patient Rooms
- Labor/Delivery Recovery
- Neuro and Ortho ICU
- NICU
- Nurse Stations
- Pharmacy (Retail & Compounding)
- PT/OT
- Skilled Nursing
- Sleep Labs

Product Information

Nominal Dimensions:

Available as a standard in rolls. Talk to your local agent to determine availability, pricing, minimums, and lead times.



Rolls:
6' (1.83 m) x 30' (9.14 m)
Thickness: 7mm nominal
(2 mm surface layer + 5 mm VCR base layer)

[View products and colors](#)

Visual Options:

Cosmos Rx - solid colors with pearlescent fragments, available in 6 colors.
Crossings Rx - contemporary textile pattern available in 8 colors.
Forest Rx - true wood visual, available in 17 colors.
Infinity Rx - linear pattern, available in 9 colors.
Strait Rx - linen appearance, available in 6 colors.

THE NRG FACTOR

NRG

=

>>>

11.5%

Force Reduction

Absorption of impact energy

>>>

72.0%

Energy Restitution

Useful return of impact energy

Safety

Ergonomics

Acoustics

Technical Details

Performance Criteria	Test Standard	Typical Results
Recovery after Static Load (@400psi)	ASTM F970 modified	0.004"
Recovery after Static Load (@1000psi after 96 hours)	ASTM F970 modified	0.004"
Coefficient of Friction	ASTM D2047	>0.6
FloorScore	CA01350	Certified
Flammability - Critical Radiant Flux	ASTM E648	Class I
Abrasion Resistance	ASTM D3389	Pass
Dynamic Rolling Load	ASTM F2753	No change, no damage (@10,000 cycles)
Sound Transmission Class (STC)*	ASTM E90	56
Impact Insulation Class (IIC)*	ASTM E492	52
Delta IIC*	ASTM E2179	23
Floor Impact Sound	ASTM E3133	77dBA

* Tested on a 6" concrete slab with no ceiling.

ecosurfaces.com • 833-888-1760

BUILT ON

itsTRU[®]

TECHNOLOGY

eco

surfaces